



PRODUCT PAGE

3-POINT FELLING DOGS

WHAT MAKES THE WESTCOAST SAW FELLING DOGS DIFFERENT THAN OTHERS ON THE MARKET?

The Westcoast Saw 3-Point Felling Dogs are designed with functionality in mind. The middle spike falls directly in line with the chain kerf, allowing for a smoother cut and great articulation, especially when bucking or lining up face cuts.



PROPRIETARY
STEEL



STRONGER THAN
FACTORY



MADE IN THE USA



AGGRESSIVE DESIGN



SMOOTHER CUT



MOST COMMON FELLING DOG CUSTOMER QUESTIONS

Why do I need to run a chain catcher on your dual-felling dogs?

With any oversized dual-felling dog set-up, the chain catcher is necessary for added strength against the force of twisting. We provide a 6-month warranty against breakage when used with a chain catcher.

Is a chain roller included with my 3-point felling dogs?

Husqvarna®, Makita®, and Echo® dual-felling dog models include a chain catcher.

Stihl® compatible felling dogs and single spike dogs do not include a chain catcher.

Is hardware included with my 3-point felling dogs?

Felling dog hardware is not included (exception is Echo model 100-0223 - hardware is included)

You can reuse the OEM hardware if you're already running dual dogs. If drilling through your clutch cover, you may need 14-16MM bolts. If your clutch cover has pre-drilled holes, 12MM bolts should be sufficient.

INSTALLATION TIPS

General Installation for dual-felling dogs

- 1 Remove the clutch cover and install the inside felling dog. Make sure the bolts are tightened.
- 2 Some factory clutch covers may not have predrilled holes. If necessary, drill out the pre-marked hex marks on the clutch cover below the chain sliders and install the outside felling dog. Install the bolts inside facing out; the nut will be placed on the outside. Put on loosely.
- 3 Attach the chain catcher to the outside felling dog.
- 4 Place the assembled clutch cover on the bar studs. Once the chain catcher is aligned to the inside dog hole, tighten the outside felling dog bolt.

Insider Tip

Customers may lose up to an inch of bar length with some of the 3-point felling dogs.

The 3-Point felling dogs for the 462 (part number 100-0217) is a replica of part number 100-0206, but slightly smaller. We recommend these to customers who prefer a smaller-scale version of the 100-0206.



SUGGESTED YOUTUBE VIDEOS:



3-POINT, 4-POINT, AND 5-POINT FELLING DOGS – WHAT'S THE DIFFERENCE?



INSTALLING A CHAIN CATCHER